

BLACKMER® ROTARY HAND PUMPS

Leading manufacturer of hand pumps since 1901. An ISO 9001 certified company. Blackmer® rotary hand pumps provide a safe, convenient method of dispersing or transferring non-corrosive liquids from drums, barrels, tanks or vats. Designed for easy, efficient operation in handling a wide range of liquids in industrial, construction & agricultural applications.



Rotary Hand Pump Features:

- Positive displacement
- Self-priming design
- Low-friction, chemically inert vanes
- Rugged, durable cast iron head / cylinder
- Handles Class I and II Flammable and combustible liquids, FM approved



Typical applications: dispensing light to medium cutting oils, solvents, and fuels.

Model No.	Description	Cap. @ 115 rev's.	Max Viscosity	Port Size (NPT)	Weight (Lbs.)	Unit Price
GENERAL TRANSFER						
PA210A	Basic Pump	10 gal.	420 Cs.	3/4"	14	
AT210A	Pump, Bung Adapt., Spout, Suct. Pipe (2 pcs.)	10 gal.	420 Cs.	3/4"	19	
BR210A	Pump, Adapt., Spout, 5/8"x8' Hose, Nozzle, Suct. Pipe	10 gal.	420 Cs.	3/4"	20	

Typical applications: FM Approved for handling Class I & II flammable / combustible liquids.

Model No.	Description	Cap. @ 115 rev's.	Max Viscosity	Port Size (NPT)	Weight (Lbs.)	Unit Price
FLAMMABLE/COMBUSTIBLE FLUID TRANSFER						
BRF210A	FM Appr. Pump, Adapt., Spout, 3/4"x8' Hose, Nozzle, Vacuum Breaker, Suct. Pipe (2 pcs.)	10 gal.	420 Cs.	3/4"	24	
DPF210A	FM Pump, Spout, Drip Pan, Telescoping Suct. Pipe	10 gal.	420 Cs.	3/4"	28	

Typical applications: (rapid transfer) fuel, lube oils and non-corrosive industrial process fluids.

Model No.	Description	Cap. @ 115 rev's.	Max Viscosity	Port Size (NPT)	Weight (Lbs.)	Unit Price
HEAVY DUTY TRANSFER						
PA414B	Basic Pump	14 gal.	2200 Cs.	1/4"	20	
AT414B	Pump, Bung Adapter, Spout, Suct. Pipe (2 pcs.)	14 gal.	2200 Cs.	1/4"	31	
BR414B	Pump, Adapt., Spout, 1"x8' Hose, Nozzle, Vac. Brkr., Pipe	14 gal.	2200 Cs.	1/4"	36	

Typical applications: (heavy liquids) transferring/dispersing grease, resins, glucose, etc.

Model No.	Description	Cap. @ 115 rev's.	Max Viscosity	Port Size (NPT)	Weight (Lbs.)	Unit Price
HEAVY DUTY VISCOUSS FLUID TRANSFER						
PA807B	Basic Pump (Low-Geared Drive)	7 gal.	6300 Cs.	1/4"	32	
AT807B	Pump, Bung Adapter, Spout, Suct. Pipe (2 pcs.)	7 gal.	6300 Cs.	1/4"	44	
BR807B	Pump, Adapt., Spout, 1"x8' Hose, Nozzle, Vac. Brkr., Pipe	7 gal.	6300 Cs.	1/4"	52	

Typical applications: (fast, high-volume output) commonly used for refueling construction equipment, etc.

Model No.	Description	Cap. @ 115 rev's.	Max Viscosity	Port Size (NPT)	Weight (Lbs.)	Unit Price
HEAVY DUTY HIGH VOLUME TRANSFER						
PA828B	Basic Pump (High-Geared Drive)	28 gal.	1050 Cs.	1/4"	32	
AT828B	Pump, Bung Adapt., Spout, Suct. Pipe (2 pcs.)	28 gal.	1050 Cs.	1/4"	44	
BR828B	Pump, Adapt., Spout, 1"x8' Hose, Nozzle, Vac. Brkr., Pipe	28 gal.	1050 Cs.	1/4"	52	