

QWIK-FENCE® WELDED WIRE PARTITIONS

SPECIFICATIONS



Qwik Fence's component system makes planning, installing and relocation easy.

Qwik-Fence® is a tough but attractive partitioning system for securing any space.

Panels 8-gauge galvanized welded wire mesh with 1½" x 3" grid openings and 1" bends on top and bottom. Stack panels to create heights of 20' and over.

Posts 2" x 2" x 14-gauge galvanized steel welded to 7" x 2¼" mounting plate.

Hinged Doors

8-gauge galvanized welded wire mesh with 1½" x 3" grid openings. Pre-hung with 94" clear height opening.

Sliding Doors

8-gauge galvanized welded wire mesh with 1½" x 3" grid openings. Pre-hung with 96" clear height opening. Both single and double sliding doors available.

Dutch Doors

8-gauge galvanized welded wire mesh with 1½" x 3" grid openings. Pre-hung with 96" clear height opening.

Locking Built-in cylinder lock keyed different (KD), pre-installed, or padlock hasp.

Hardware All necessary hardware included.

Finish Galvanized.

Options Keyed alike cylinders (KA), Double cylinders (DC), ADA-compliant locks, Push button locks, Electric strike/card reader style locks and Interlock switches.

Crash/panic bars, Spring hinges and automatic closures.

Service window.

Powder coating finish.

Warranty 1 year.

Solution Dynamics Inc
PO Box 866
Brookfield WI 53008
PH: 262-521-5730
FX: 262-521-5733
www.sodyinc.com
email: sdi@sodyinc.com

Qwik-Fence® Welded Wire Partitions

Standard Components

	Part No.	Wgt. (lbs.)
Panels 1½" x 3" grid opening		
8'x 4'	8x4	29
8'x 3'	8x3	23
8'x 2'	8x2	16
8'x 1'	8x1	9

Posts

8' Universal post	P8	20	Includes mounting plate
8' Post flat	P8 Flat	25	
8' Post flat/offset	P8 Flat/Offset	25	
1' Extension Post	XP1	4	
2' Extension Post	XP2	6	
3' Extension Post	XP3	8	
4' Extension Post	XP4	10	
6' Extension Post	XP6	17	
8' Extension Post	XP8	19	

Options

Roof Support Center Tube	RST	2	Per linear foot
Ceiling Wall Angle	CA8	5	8' length
Wall Kit	WK	8	Attaches panel to wall
Service Window Kit	SWK	55	Provides thru door access
Post Top Extension	PXT	5	To securely extend posts
Header 2"x2"	H22-48		Ties posts horizontally

Options, continued

	Part No.	Wgt. (lbs.)
Capping Channel 96"	Consult factory	Ties posts horizontally
Diagonal Brackets	HD-RFCMT	
8' Door Transom Kit	TK-10	3 Fits 8' door into 10' frame
10' Door Transom Kit	TK-12	6 Fits 10' door into 12' frame
ADA Handle (inside)	H-ADA	4
Panic Bar	Consult factory	
Hinged Door Hardware	H-PANIC	11
Electric Strike/Keypad	Consult factory	
Hinged Door Hardware	H-ELECT	3.5
BEST Key-in-Knob Lockset	Consult factory	
Hinged Door Hardware	H-BEST	9
Interlock Switch	Consult factory	
Clear Access Door	Consult factory	
Vertical Slide Door	Consult factory	
Swinging Gate Lock	W3710	2
Sliding Gate Lock	W3810	2
Exterior Knob Assembly	WA9251	2
Interior Lever Cover	WA9292	2
Lever Stop Plate	W3791	1
Powder Coating	Consult factory	
Wire Cutter	WIR CUTR	5 Industrial grade

Stock Doors

WIDTH	8' HIGH		10' HIGH		12' HIGH	
	Part No.	Wgt. (lbs.)	Part No.	Wgt. (lbs.)	Part No.	Wgt. (lbs.)
Hinged Door						
3'	H-3	64	Consult factory		Consult factory	
4'	H-4	75	Consult factory		Consult factory	
Hinged Door (Pair)						
3' each	HP6-8	160	Consult factory		Consult factory	
4' each	HP8-8	190	Consult factory		Consult factory	
Dutch Door						
3'	D-3	121	Consult factory		Consult factory	
Slide Door						
3'	S3	88	Consult factory		Consult factory	
4'	S4	100	S-410	129	S-412	155
5'	S5	132	S-510	160	S-512	192
6'	S6	143	S-610	178	S-612	211
8'	S8	170	S-810	273	S-812	328
10'	S10	249	S-1010	308	S-1012	367
Slide Door (Pair)						
8'	SP8-8	236	SP8-10	279	SP8-12	335
10'	SP10-8	265	SP10-10	312	SP10-12	374

Solution Dynamics Inc
 PO Box 866
 Brookfield WI 53008
 PH: 262-521-5730
 FX: 262-521-5733
 www.sodyinc.com
 email: sdi@sodyinc.com