



MODELS 3230K24CS / 4230K28CS

3 HP TWO STAGE TWO CYLINDER PORTABLE ELECTRIC COMPRESSORS



MODEL 3230K24CS

ROLAIR STANDARD FEATURES

PUMP: Two Stage, Enbloc Cast-Iron Cylinders, Ball Bearings, Splash Lubricated, Automotive-Style Bearing Inserts on Connecting Rods, High Efficiency Reed Valves, Oil Sight Gauge, Low RPM to Ensure Long Life and Trouble-Free Performance.

MOTOR: 3 HP 1740 RPM Open Drip-Proof
230 Volts, 60 Hz Ball Bearings
Overload Protected with Manual Reset

PERFORMANCE @ 100 PSI:
Cu. Ft. Displaced - 18.4—3230K24CS
Cu. Ft. Free Air - 12.1—3230K24CS
Cu. Ft. Displaced - 19.2—4230K28CS
Cu. Ft. Free Air - 14.9—4230K28CS

TANK ASSEMBLY: Non-Code, 9 Gallons

WHEELS: Two 410/350 x 4
2-Ply Fully-Pneumatic *with Sealant*

DIMENSIONS:
L46" x W27" x H29" - 3230K24CS
L46" x W27" x H30" - 4230K28CS

APPROXIMATE SHIPPING WEIGHT: 270 lbs.—3230K24CS
270 lbs.—4230K28CS

STANDARD EQUIPMENT

- Constant Speed with Pilot Unloader
- Universal Quick Disconnect Fitting
- Totally Enclosed Steel Belt Guard
- Accessory Support Bracket
- Pressure Gauge 0-300 in 5 lb. Graduations
- 120/150 PSI Operating Pressure
- Safety Relief Valve
- Air-Cooled Intercooler

OPTIONAL EQUIPMENT

20 Gallon ASME Receiver, Filter-Regulator-Lubricator Sets