



MODEL 6820K17

**2 HP SINGLE STAGE TWO CYLINDER
PORTABLE ELECTRIC COMPRESSOR**



ROLAIR STANDARD FEATURES

PUMP: ROLAIR Quality, Heavy-Duty, Single Stage, Ball Bearings, Cast-Iron Twin Cylinders, Hardened Steel Valve Plates with Swedish Lamellar Reed Valves, Aluminum Alloy Connecting Rods with Automotive-Style Inserts, Multi-Finned 11" Flywheel, Oil Sight Gauge and Splash Lubrication.

MOTOR: 2 HP 1740 RPM Open Drip-Proof
115/230 Dual Voltage Switch
Overload Protected with Manual Reset

PERFORMANCE @ 100 PSI:
Cu. Ft. Displaced - 12.5
Cu. Ft. Free Air - 8.4

TANK ASSEMBLY: Non-Code, 9 Gallons

DIMENSIONS:
L46" x W19" x H28"

WHEELS: One 410/350 x 4 *Flat-Free Tire*

APPROXIMATE SHIPPING WEIGHT:
174 lbs.

STANDARD EQUIPMENT

- Industrial Square D Pressure Switch with Relief Valve
- Intake Filter with Silencer and Replaceable Element
- Universal Quick Disconnect Fitting
- Totally Enclosed Steel Belt Guard
- Accessory Support Bracket
- Pressure Gauge 0-200 in 5 lb. Graduations
- 110/135 PSI Operating Pressure
- Safety Relief Valve
- Air-Cooled Aftercooler

OPTIONAL EQUIPMENT

Constant Speed Operation, Dual Control Operation, Filter-Regulator-Lubricator Sets, 20 Gallon Tank