



**MODELS D2002HPV5 / ~~D2002HSSV5~~**  
**2 HP SINGLE STAGE COMPRESSOR**  
**DIRECT DRIVE**



**MODEL D2002HPV5**



**MODEL D2002HSSV5**

**ROLAIR STANDARD FEATURES**

**PUMP:** ROLAIR Quality, Heavy-Duty, Single Stage, Ball Bearings, Cast-Iron Cylinder, Metal Filter/Silencer with Replaceable Filter Element, Stainless Steel Reed Valves and Splash Lubrication Ensure Longer Life.

**MOTOR:** 2 HP, 3400 RPM, Low Amp Draw Overload Protection with Manual Reset, 115 Volt, 60 Hz, Heavy-Duty/Industrial Grade with Ball Bearings for Greater Durability.

**SPECIFICATIONS**

MODEL	MOTOR HP	# OF CYLS.	CU.FT. DISPLACED	CU.FT. FREE AIR@100 PSI	TANK CAP. (GAL.)	DIMENSIONS (L X W X H)	APPROX SHIPPING WEIGHT
D2002HPV5	2	1	7.8	4.0	4.5	18" X 16" X 17"	62 lbs.
D2002HSSV5	2	1	7.8	4.0	4.3	20" X 15" X 17"	68 lbs.

**STANDARD EQUIPMENT**

- Square D Pressure Switch with On/Off Lever
- Air Line Regulator and Pressure Gauge
- Universal Quick Disconnect with Plug
- 110/135 PSI Operating Pressure
- Factory Tested
- 14.2 Amp Motor
- Safety Relief Valve
- 12 oz. Crankcase Pre-Filled with Oil