



## MODEL V3160K18 3 HP SINGLE STAGE COMPRESSOR



### ROLAIR STANDARD FEATURES

**PUMP:** Single Stage, Cast-Iron Cylinders, Aluminum Head and Crankcase for Faster Heat Dissipation, Ball Bearings, Splash Lubricated, Bearing Inserts on Connecting Rods, High Efficiency Reed Valves, Oil Sight Gauge, Low RPM's to Ensure Long Life and Trouble-Free Performance. **For Pump Specifications See Reverse Side**

**TANK :** Horizontal or Vertical  
60 Gallon - ASME

**APPROXIMATE SHIPPING WEIGHT:**  
265 lbs.

**MOTOR:** Open Drip-Proof  
220 Volt – 60 Hz – 3450 RPM - 1 Phase  
230/460 Volt – 60 Hz – 1725 RPM - 3 Phase

### STANDARD EQUIPMENT

- Pressure Switch - Start-Stop Operation 110-135 PSI Settings, On/Off Switch
- Automatic Unloading Device for Loadless Starts
- Heavy-Duty Brass Shut-Off Valve
- Pressure Gauge - 0-200 PSI in 5 lb. Graduations
- Safety Relief Valve - ASME Approved
- V-Belt Drive
- Intake Filter/Silencer with Replaceable Element
- Totally Enclosed Steel Belt Guard

### OPTIONAL EQUIPMENT

Magnetic Starter, Automatic Tank Drain, Low Oil Shutdown, Level Rite Mounts, Vibration Pads, 208V Motor, Dual Controls, Head Unloader, Air-Cooled Aftercooler, Refrigerant Air Dryer



### ROLAIR SYSTEMS

606 S. LAKE ST > P O BOX 346 > HUSTISFORD WI 53034-0346  
SALES FAX: 920.349.3691 > SERVICE FAX: 920.349.8861  
PHONE: 920-349-3281

[www.rolair.com](http://www.rolair.com)

# MODEL PMP12K18CH



K18

## SPECIFICATIONS

NO. OF CYLINDERS	CYLINDERS BORE & STROKE (inches)	OIL CAPACITY (oz.)	FWHL DIAMETER (inches)	DRY WEIGHT (lbs.)	MAXIMUM PRESSURE
2	(2) 2.75 x 1.97	34	11	37.5	150 PSI

## PERFORMANCE

HP	DISCHARGE PRESSURE	CFM DISPLACED @ 100 PSI	CFM DELIVERED @ 100 PSI	PUMP RPM
3	100 PSI	13.8	11.9	1100