



MODEL VT20TB
2 HP SINGLE-STAGE COMPRESSOR
DIRECT DRIVE
LOW SPEED ~ QUIET



ROLAIR STANDARD FEATURES

PUMP: **Low Speed ~ Quiet**, ROLAIR Quality, Cast-Iron Cylinder, Single Stage, Ball Bearings, Stainless-Steel Reed Valves and Splash Lubrication Ensure Longer Life.

MOTOR: 2 HP, 1700 RPM, S1-Rated for Continuous Duty, Low-Amp Draw, Overload Protection with Manual Reset, 115 Volt, 60 Hz, Heavy-Duty/Industrial Grade with Ball Bearings for Greater Durability.

SPECIFICATIONS

MODEL	MOTOR HP	# OF CYLS	CU.FT. DISPLACED	CU.FT. DELIVERED @ 90 PSI	TANK CAP. (GAL.)	DIMENSIONS (L X W X H) (INCHES)	APPROX. SHIPPING WT. (LB.)
VT20TB	2	1	5.5	4.2	3.2	18 x 19 x 37	80

STANDARD EQUIPMENT

- 100% Duty-Cycle Motor
- Reduced Operating Noise Due to Low-Speed Motor
- Start/Stop Pressure Switch with On/Off Lever
- Dolly-Cart with Wheels for Easy Maneuvering
- User-Friendly Control Panel Including Gauges, Two Quick-Disconnect Couplers and Air Regulator
- Tool Box for Convenient Jobsite Storage
- Safety-Relief Valve
- Intake Filter Silencer
- 12.3-Amp Motor
- Initial 10-oz. Oil Fill Included

