



END DRIVE, BOTTOM RIGHT HAND (SHOWN)
END DRIVE, BOTTOM LEFT HAND (OPPOSITE)




SECTION A-A
TAKE-UP END
TYPICAL ALL DRIVES




SECTION B-B
DRIVE END

SPECIFICATIONS	
BELT WIDTH: 12", 18", 24", 30", 36"	
BEGINNING ELEVATION: 4.5" - 60"	LENGTH: 48" - 600"
ENDING ELEVATION: 4.5" - 60"	SPEED: 15 - 300 FPM
BELT: Standard is Trackmate 120 EMB embossed cover with clipper lace. <u>Optional</u> belts include Trackmate rough top, Trackmate friction cover, Trackmate longitudinal groove, food grade white PVC & plied rubber slip top. Other belt options available.	
DRIVE: Standard drive is an end drive, bottom right hand. <u>Optional</u> drives include end drive, bottom left hand; side drive right or left hand; or center drive right or left hand.	
MOTOR: 1/2 HP through 1-1/2 HP. Energy efficient, inverter duty, brake motors also available. Voltages include 120/1/60, 230/3/60, 460/3/60, 575/3/60 & DC voltage.	
SUPPORT CENTERS: Standard supports are floor supports on 10' centers. <u>Optional</u> floor supports on 5' centers; ceiling supports on 5' & 10' centers.	
GUARDRAIL: <u>Optional</u> 2.5", 4.0" & 6.0"; 12ga bolt on channel.	
FRAME FINISH: Standard finish is OSHA safety blue powder. <u>Optional</u> colors include green, beige, gray, orange, black & yellow.	


Model: 40SB - Low Profile Slider Bed Belt Conveyor




**CENTER DRIVE, RIGHT HAND (SHOWN)
CENTER DRIVE, LEFT HAND (OPPOSITE)**




**SIDE DRIVE, RIGHT HAND (SHOWN)
SIDE DRIVE, LEFT HAND (OPPOSITE)**




CENTER DRIVE OPTION



**CENTER DRIVE
END VIEW**



SIDE DRIVE OPTION



**SIDE DRIVE
END VIEW**

LOAD CAPACITY @ 60 FPM (LBS)

HP	WIDTH				
	12"	18"	24"	30"	36"
1/2	290	285	280	270	265
3/4	445	440	435	425	420
1	600	590	585	580	570
1 1/2	900	895	885	880	870


LOAD CAPACITY @ 30 FPM (LBS)

HP	WIDTH				
	12"	18"	24"	30"	36"
1/2	600	595	590	580	575
3/4	910	900	895	890	880
1	1215	1205	1200	1195	1185
1 1/2	-	1820	1810	1805	1800

MAXIMUM LOAD PER LINEAR FOOT OF CONVEYOR IS 75 POUNDS - NOT TO EXCEED CAPACITY ABOVE

GUARDRAIL OPTION

A
2.5"
4.0"
6.0"



12ga BOLT ON CHANNEL