



# MODEL 5230K30CS

## 5 HP TWO STAGE TWO CYLINDER PORTABLE ELECTRIC COMPRESSOR



### ROLAIR STANDARD FEATURES

**PUMP:** Two Stage, Enbloc Cast-Iron Cylinders, Ball Bearings, Splash Lubricated, Automotive-Style Bearing Inserts on Connecting Rods, High Efficiency Reed Valves, Oil Sight Gauge, Low RPM to Ensure Long Life and Trouble-Free Performance.

**MOTOR:** 5 HP 1740 RPM Open Drip-Proof  
230 Volts, 60 Hz Ball Bearings  
Overload Protected with Manual Reset

**PERFORMANCE @ 100 PSI:**  
Cu. Ft. Displaced - 23.1  
Cu. Ft. Free Air - 17.9

**TANK ASSEMBLY:** Non-Code, 9 Gallons

**DIMENSIONS:**  
L46" x W27" x H34"

**WHEELS:** Two 410/350 x 4  
2-Ply Fully-Pneumatic *with Sealant*

**APPROXIMATE SHIPPING WEIGHT:**  
296 lbs.

### STANDARD EQUIPMENT

- Constant Speed with Pilot Unloader
- Universal Quick Disconnect Fitting
- Totally Enclosed Steel Belt Guard
- Accessory Support Bracket
- Pressure Gauge 0-300 in 5 lb. Graduations
- 120/150 PSI Operating Pressure
- Safety Relief Valve
- Air-Cooled Intercooler

### OPTIONAL EQUIPMENT

20 Gallon ASME Receiver, Filter-Regulator-Lubricator Sets