



MODEL 7722HK28

9 HP TWO STAGE TWO CYLINDER PORTABLE GAS COMPRESSOR



ROLAIR STANDARD FEATURES

PUMP: Two Stage, Enbloc Cast-Iron Cylinders, Ball Bearings, Splash Lubricated, Automotive-Style Bearing Inserts on Connecting Rods, Swedish Lamellar Reed Valves, Cast-Iron Valve Plates, Oil Sight Gauge and Intercooler.

ENGINE: 9 HP Honda 4 Cycle, Complete Aluminum Alloy with Cast-Iron Sleeve, Overhead Valves, Retractable Starter, On/Off Switch, Splash Lubricated, Low Oil Shutdown

TANK ASSEMBLY: Non-Code, 9 Gallons
I-Beam Saddle Construction

WHEELS: Two 410/350 x 4
2-Ply Fully-Pneumatic *with Sealant*

PERFORMANCE @ 100 PSI:

Cu. Ft. Displaced - 20.3

Cu. Ft. Free Air - 16.2

DIMENSIONS:

L46" x W28" x H30"

APPROXIMATE SHIPPING WEIGHT:

276 lbs.

STANDARD EQUIPMENT

- Automatic Pilot Valve Operation
- Industrial Flexible Discharge Hose
- Automatic Idle Control for Economy and Long Service Life
- Accessory Support Bracket
- Engine Oil Drain Port in Saddle
- 120/150 PSI Operating Pressure
- Pressure Gauge 0-300 in 5 lb. Graduations
- Schmidt Belt Tightening Device
- Safety Relief Valve
- Totally Enclosed Steel Belt Guard
- Universal Quick Disconnect Fitting

OPTIONAL EQUIPMENT

Filter-Regulator-Lubricator Sets, Electric Start (Honda and Kohler),
20 Gallon ASME Tank, Kohler and Robin Engines, Battery Tray